

规格承认书

Specification for approval

产品名称: FLF 大电流方形慢熔汽车保险丝

**Product Type: FLF 30 High Amp Female Termination Slow
Blow Fusible Auto Fuse Link 32V 30A Pink For
Japanese-designed Vehicles**

Ao littel Technology Co.Ltd.

Bld. 16, Yanhe East Road, Xiangdong Village, Dongguan 523833,
Guangdong, China

H.P.: 1371362419

Fax #: 0769-89390418

QQ #: 3217998702

Email: eric.lye@aolittel.com

<http://www.passivemall.com/>

<http://www.aolittel.com/>

1. Scope

Designed to meet aftermarket OEM requirements , offering high ampere 20A-100A ratings in compact package.Operation standards: JASO D612 / ISO 8820-4 . FLF Series Female Terminal Fusible Links are used primarily in Japanese-designed vehicles for wiring harness protection .Color-coded molded plastic housing allows quick identification of amp rating.30 Amp (Pink), 32 Vdc.Includes convenient viewing window for verifying link status.Sold individually.









2. Specifications

Slow-Blow Auto Fuse Link	
Voltage Rating : DC32V or less	
Interrupting Rating:	1000A @32VDC
Material	1. Brass 2. Nylon With Glass Fiber / PC 3. Ceramic
Standard	Complies with JASO D612 / ISO 8820-4
Operating Temperature Range	-40 C to +125 C

3. Time-Current Characteristics

Test Current	Opening Time	
	Min.	Max.
110%	4 hrs.	---
150%	30 s	3600 s
200%	5 s	100 s
350%	0.2 s	7 s
600%	0.04 s	1 s

4. Electrical Performances

Item No.	Ampere	Color
FLF 20	20 A	
FLF 30	30 A	
FLF 40	40 A	
FLF 50	50 A	
FLF 60	60 A	
FLF 70	70 A	
FLF 80	80 A	
FLF 100	100 A	

5. Dimension (mm)

